? s pn=de 59400725 S4 1 PN=DE 59400725 ? t s4/9/1 4/9/1 DIALOG(R)File 351:Derwent WPI (c) 2003 Thomson Derwent. All rts. reserv.

010151445 **Image available**
WPI Acc No: 1995-052697/199508
XRPX Acc No: N95-041371

Machine for installation of sheet piles - has single function driving piles, with connected operating drives supported or suspended in frame

Patent Assignee: SBH TIEFBAUTECHNIK GMBH (SBHT-N)

Inventor: DEUSSEN W; THELEN W

Number of Countries: 017 Number of Patents: 006

Patent Family:

Patent No Kind Date Applicat No Kind Date Week

DE 4316824 A1 19941124 DE 4316824 A 19930519 199508 B
EP 628663 A2 19941214 EP 94106538 A 19940427 199508
EP 628663 A3 19950510 EP 94106538 A 19940427 199546
EP 628663 B1 19960925 EP 94106538 A 19940427 199643
DE 59400725 G 19961031 DE 500725 A 19940427 199649
EP 94106538 A 19940427

ES 2092845 T3 19961201 EP 94106538 A 19940427 199704

Priority Applications (No Type Date): DE 4316824 A 19930519

Cited Patents: No-SR.Pub; GB 2099478; US 3729938; US 3969904; US 4002035

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

DE 4316824 A1 9 E02D-011/00 EP 628663 A2 G E02D-017/08 EP 628663 B1 G 12 E02D-017/08

Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT LI LU MC

NL PT SE

DE 59400725 G E02D-017/08 Based on patent EP 628663 ES 2092845 T3 E02D-017/08 Based on patent EP 628663

EP 628663 A3 E02D-011/00

Abstract (Basic): DE 4316824 A

The machine has single-function driving piles (7), with a drive unit (9) for movement. The unit consists of operating drives (10), which are connected to the piles, and supported in the machine frame (2), or suspended.

The counter frame elements (6) are free of the driving piles and connected with their ends to lifting and lowering drives (11). The drives are also fastened to the machine frame, and are controlled for counter frame movement. The counter frame elements are connected at right angles to their longitudinal direction, via expander elements (12).

 $\label{eq:USEADVANTAGE-Digging} \textbf{USE/ADVANTAGE-Digging of ditches using dredgers}. \textbf{Simplified assembly and operation}.$

Dwg. 1/4

Abstract (Equivalent): EP 628663 B

A machine for the driving in and pulling of supporting wall elements (1) eg of sheet piles, when advancing trenches with the aid of an excavator, having a machine frame (2) which comprises two ground frame elements (3) disposed along the edge of the trench and running in the longitudinal direction of the trench, and tie-bars (4) joining the ground frame elements (3), and which is designed for guiding the supporting wall elements (1), a counterframe (5), which comprise two counter-frame elements (6), which are disposed in the cut trench, which

run in the longitudinal direction of the tench, which are raisable and lowerable in the trench, and on which the supporting wall elements (1) can be supported a driving beam (7) disposed in the machine frame (2) at each trench edge side, which driving beams extend in the longitudinal direction of the trench and can be attached individually or jointly by attachment devices to the supporting wall element (1) to be driven in or to be pulled, wherein the driving beams (7) are disposed in the machine frame (2) and are raisable and lowerable with the aid of drive devices (9), characterised in that the combination of the following features is put into effect, (a) the driving beam (7) are single-function driving beams and possess a drive device (9) for the travel of the driving beams, which drive device comprises adjusting drives (10), which are disposed in the region of the ends of the driving beams (7) which are attached on one side to the driving beams (7) and are supported or suspended on the other side on the machine frame (2), and which are controllable for the travel of the driving beams, (b) the counter-frame elements (6) are free from the driving beam (7) and are attached in the region of their ends to raising and lowering drives (11) and are guided by the latter, which raising and lowering drives (11) are fixed on the other side to the machine frame (2) and are controllable for the travel of the counter-frame, wherein the counter-frame elements (6) are joined transversely to their longitudinal direction via stretcher elements (12).

(Dwg.1/4)

Title Terms: MACHINE; INSTALLATION; SHEET; PILE; SINGLE; FUNCTION; DRIVE; PILE; CONNECT; OPERATE; DRIVE; SUPPORT; SUSPENSION; FRAME

Derwent Class: Q42

International Patent Class (Main): E02D-011/00; E02D-017/08

File Segment: EngPI